



EWA 10

- Torque 50 Nm. Speed 3 ñ 5 rpm.
- Two-stage helical worm gear unit, self-locking with long service life.
- Standard fastening at back or sides (symmetrical, left) for easy mounting anywhere!
- Built-in precision gearwheel limit switch E 20 for 580 shaft revolutions (UL + CSA standard).
- High-quality motors, multi-range voltage (IEC 38) for 50 Hz (380 - 420 / 220 - 240 V) and 60 Hz (380 - 480 / 220 - 280 V). ED = 40 %, IP 55, isol. class F. Other voltages available on request.
- All single phase motors with integrated coil safety contact, no separate motor protection switch necessary. Pre-wired with 4 m cable.
- Options: safety limit switch E20S, position repeater PA 6, version A60 for external installation.



EWA 12

- Torque 70 - 250 Nm. Speed 1,6 ñ 8,8 rpm.
- Extremely quiet, self-locking double worm gear unit with long service life.
- Standard fastening at back or sides (symmetrical, left) for easy mounting anywhere! Removable brackets.
- Built-in precision gearwheel limit switch E20 for 580 shaft revolutions (UL + CSA standard).
- High-quality motors, multi-range voltage (IEC 38) for 50 Hz (380-420/220 -240 V) and 60 Hz (380 - 480 / 220 - 280 V). ED = 40 %, IP 55, isol. class F. Other voltages available on request.
- All single phase motors with integrated coil safety contact, no separate motor protection switch necessary. Pre-wired with 4 m cable.
- All types with shaft We 66 or shaft We 06 available.
- Options: safety limit switch E20S, position repeater PA6, version A60 for external installation.



EWA 14

- Torque 350 - 600 Nm. Speed 1,6 ñ 8,8 rpm.
- Extremely quiet, self-locking double worm gear unit with long service life.
- Standard fastening at back or sides (symmetrical, left) for easy mounting anywhere! Removable brackets.
- Built-in precision gearwheel limit switch E20 for 580 shaft revolutions (UL + CSA standard).
- High-quality motors, multi-range voltage (IEC 38) for 50 Hz (380-420/220 -240 V) and 60 Hz (380 - 480 / 220 - 280 V). ED = 40 %, IP 55, isol. class F. Other voltages available on request.
- All single phase motors with integrated coil safety contact, no separate motor protection switch necessary. Pre-wired with 4 m cable.
- Standard shaft We 66, up to 450 Nm also available with shaft We 06 (power drive axial).
- Options: safety limit switch E20S, position repeater PA6, version A60 for external installation.